

L1705C

High Humidity &
Heat Resistant LED Lighting



Clear Glass Globe



Prismatic Glass Globe



With Accessory "Guard"

Standards

- UL 844
- UL 1598
- UL 8750
- CSA C22.2 No.250.0


Net Weight: 9.5 kg (20.9 lb)

*Please specify the required glass globe type.

Technical Data

▲ Illumination angle 360°


Rated Voltage (±10%)	120V / 277V AC	
Watts (±10%)	40W / 50W	
Amps	40W 120V:0.33A, 277V:0.14A / 50W 120V:0.42A, 277V:0.18A	
Color of LED Light	3000K (Warm White) / 5000K (Cool White)	
Ambient Temperature	+86°C ~ +100°C	
Power Factor	cos ≥ 0.9	
CRI	Cool White ≥ 70 / Warm White ≥ 80	
Lumen (±10%)	COB	40W / 50W
	3000K	3600lm / 4500lm
	5000K	4000lm / 5000lm
Beam Angle	X-170° / Y-170°	
Frequency	50 / 60 Hz	
Degree of Protection	IP67/ NEMA 6	
Material: Enclosure	Aluminum alloy	
LED Service Life	60,000 hrs*	
Entrance Thread	1 × NPT 3/4" or 1 x M25	




Dimension in Millimeters (inches)

Optical Report

Polar Luminous
Intensity Distribution



Luminous
Intensity Distribution Diagram



*L70 at 55°C Ambient Temperature *1 years warranty without warranting lumen depreciation.

Mounting Option & Dimensions (All in mm)

Standard Product			
<p>Wall / Hanging Mount 25° (W25)</p> <p>10.0 kg (22.0 lb)</p>	<p>Wall / Hanging Mount 90° (W90)</p> <p>10.0 kg (22.0 lb)</p>	<p>Hanging Mount 90° (H90)</p> <p>10.0 kg (22.0 lb)</p>	
<p>Straight Electrical Tube (P90)</p> <p>10.5 kg (23.1 lb)</p>	<p>Bending Electrical Tube 90° (S90)</p> <p>10.6 kg (23.4 lb)</p>	<p>Bending Electrical Tube 25° (S25)</p> <p>10.5 kg (23.1 lb)</p>	<p>Hanging Mount 25° (H25)</p> <p>10.0 kg (22.0 lb)</p>
With optional accessory "Guard"			
<p>Wall / Hanging Mount 25° (W25G)</p> <p>10.2 kg (22.5 lb)</p>	<p>Wall / Hanging Mount 90° (W90G)</p> <p>10.2 kg (22.5 lb)</p>	<p>Hanging Mount 90° (H90G)</p> <p>10.2 kg (22.5 lb)</p>	
<p>Straight Electrical Tube (P90G)</p> <p>10.7 kg (23.5 lb)</p>	<p>Bending Electrical Tube 90° (S90G)</p> <p>10.8 kg (23.8 lb)</p>	<p>Bending Electrical Tube 25° (S25G)</p> <p>10.7 kg (22.0 lb)</p>	<p>Hanging Mount 25° (H25G)</p> <p>10.2 kg (22.5 lb)</p>

THT-EX

Pulp & Paper
Glass Factory
Steel Mill
Power Plant
Recycling Plant

THT-EX

or even recycling plants, where furnaces, dryers and heaters operate at ambient temperature that is over 70°C (159°F).




LED Lighting Solutions
for High Temperature Areas


Pan Mounting Option & Dimensions (All in mm)

Retrofit Kit for C Brand


(PAN)



Installation Diagram




*Top hat is not included when placing order for retrofit pan.




10.5 kg (23.1 lb)


Retrofit Kit with optional accessory "Guard" (PANG)



Installation Diagram




*Top hat is not included when placing order for retrofit pan.




10.8 kg (23.8 lb)

Retrofit Kit for A Brand


(PANA)



Installation Diagram




Screws and Nuts are not provided.
*Top hat is not included when placing order for retrofit pan.




10.8 kg (23.8 lb)


Retrofit Kit with optional accessory "Guard" (PANAG)



Installation Diagram




Screws and Nuts are not provided.
*Top hat is not included when placing order for retrofit pan.




11.1 kg (24.5 lb)

Retrofit Kit for K Brand


(PANK)



Installation Diagram




*Top hat is not included when placing order for retrofit pan.



11.0 kg (24.3 lb)


Retrofit Kit with optional accessory "Guard" (PANKG)



Installation Diagram



*Top hat is not included when placing order for retrofit pan.



11.3 kg (24.9 lb)

Applicable Area

- Pulp & Paper Industry
- Smelter
- Automotive Industry
- Cable Manufacturing
- Power Plants
- Casthouse
- Textile Industry
- Glass Factory